

There's only one way to ensure the suspension's original performance — ask for Hendrickson genuine parts by name.

PRODUCT PROFILE

Center Bushings

CENTER BUSHING service life will vary greatly, relative to the severity of the application. Therefore, Hendrickson offers a complete line of genuine center bushings, each designed for a specific application to maximize system performance and meet user expectations. To ensure high end user satisfaction and peak system performance, Hendrickson supplies the same genuine components for service requirements as were installed in the original suspensions - with the same design, construction, performance and durability.

HIGH CONFINEMENT CENTER BUSHING

- The high confinement center bushing is standard on all 40,000-lb. capacity rated Hendrickson walking beam suspensions with rubber bushings.
- It has a higher resistance to axle walkout for a longer period of time due to the confinement of the rubber.
- This bushing is also available with a loose plug for ease of cross tube installation.
- When used in conjunction with transverse rods, the high confinement center bushing can be specified in walking beam suspensions with up to a 46,000-lb capacity rating.



BRONZE CENTER BUSHINGS

- The bronze center bushing is standard on Hendrickson's 46,000-lb. and 52,000-lb. capacity walking beam suspensions.
- It is primarily used in the most severe applications, such as high-capacity suspensions that encounter extremely tight turns under heavy loads.
- This bushing requires that recommended maintenance procedures be performed to promote extended service life and performance.
- Bronze center bushings should not be used with transverse torque rods and must not be used in aluminum beams.



FULLY BONDED CENTER BUSHINGS

- Hendrickson's fully bonded center bushing provides the extra strength and durability necessary to routinely handle heavy loads.
- It is designed for high capacity suspensions rated to 52,000-lb. capacities, where low maintenance and low tire wear are valued benefits.
- Transverse rods are mandatory with this bushing.



For The Road Ahead

 **HENDRICKSON**

Visit us at www.hendrickson-intl.com

